



Description		Commercial refrigerator		
Model Number		BR-1261HP (AUH)		
Dimensions	Overall Dimension (W X D X H)	1200mm	600+(40) mm	850mm
	Outside Dimension (W X D X H)	794mm	437mm	573mm
Effective Volume		214 L		
Material	Overall Material	Stainless Steel Plate OUT:TTS443M-NO.4		
	Door	Stainless Steel Plate OUT:TTS443M-NO.4		
	Inner Material	Stainless Steel Plate IN: JYH21CT-2B		
	Net Rack	P E . and painted steel wire footings		
	Insulation	Cyclopentane Horniness Froth		
Performance	Condition	External Temperature 30°C With no load not exposed to direct sunlight		
	Internal Temperature	Below 3°C		
Temperature Setting Range		-2 ~ 10°C		
Freezing Assembly	Compressor	Obturation Completed		
	Condenser	Fin Type Forced Circulation Of Cold Air		
	Evaporator	Fin Type Forced Circulation		
	Refrigrant	R290		
	Fan Motors	Evaporator	Single Phase INPUT DC 12V 6W	
		Condenser	Single Phase INPUT DC 12V 8.4W	
	Tem. Meter	Mini Computer Controlled		
Defrost	Mini Computer controlled ,Auto heat desfrost			
Power Specification	Power	Single-Phase 220-240V 50HZ		
	Efficiency Consumption	Defrosting 247W		
		Cooling 260W		
Power	Power Cord	Lenth: 3.0m		
	Applicable Socket	2-plug with gronging end 10A 250V		
Table Foot	Colophony Control Bound 130mm			
Accessories	2 Net rack, 5 net rack support.			
Others	Condenser Filtnet , figure thermometer			
Weight	88 kg			

Note: 1. For the output power. The electromotor normal stipulatlated output power.
 2. Please use this numerical value , if you want to express the electrical expender .

Panasonic Appliances Cold Chain (Dalian) Co., Ltd	APPROVALS	DESIGN	SCALE			PART CODE	
	Li Fei 2022.02.21	Lan Shaojuan 2022.02.21	A4	SUR-1261HP (AUH)-00		PRODUCT NAME	BR-1261HP(AUH)
			1/30	DATE	2022.02.01		