

Galaxy H150 TN Open



H 150

P 88

L 94 • 125 • 188

sandwiches • drinks • dairy • fresh products

Open front semi-vertical multideck chiller, fitted with an environmentally friendly plug-in R290 refrigeration system for the display of dairy products, fresh and pre-packed products

Installation

Plug-in

Cabinet Front Height

427 mm

Configuration

Semi Vertical Open Front

Refrigerant

R290

Refrigeration System

Ventilated (RV)

Compressor

Hermetic

Defrost

Off cycle

Temperature Range

0 / + 2 °C

Climate Class

3M1

Operating Conditions

25°C Ambient / 60% RH

Power Supply

230V / 1 Ph / 50Hz

Electrical Amperage 94

10A

Electrical Amperage 125

10A

Electrical Amperage 188

20A

Closing System

Open Front -
Self Rolling Curtain

Side Panels

- Panoramic End Panel - safety glass (Std)
- Solid Mirror End Panel (Optional)

Shelves No.

3 with LED (Lighting Standard)

Shelves Type

Solid

Shelves Fence

Perspex (Std)

Lighting

- 4000K LED Canopy (Std)
- 4000K Undershef LED Shelf (Std)
- 3000K LED Colour (Optional)

Inside Colour

RAL 9005 - Jet Black (Std)

Outside Colour

RAL 9005 - Jet Black (Std)

Side Panels Colour

RAL 9005 - Jet Black (Std)

Base/ Equipment Handling

- Castors with brake (Std)
- 4 adjustable feet (optional)



Open Front Low Height Merchandiser

Inside colour



Outside Colour



Side panels colour



RAL colour system or stainless steel options available ex. factory *POA



Galaxy H150 TN Open

		94	125	188
External Dimensions PANORAMIC (LxDxH)	Swivel Castors	993 x 908 x 1575 mm	1300 x 908 x 1575 mm	1935 x 908 x 1575 mm
	Adjustable Feet	993 x 908 x 1510 mm	1300 x 908 x 1510 mm	1935 x 908 x 1510 mm
External Dimensions SOLID (LxDxH)	Swivel Castors	1011 x 908 x 1575 mm	1318 x 908 x 1575 mm	1953 x 908 x 1575 mm
	Adjustable Feet	1011 x 908 x 1510 mm	1318 x 908 x 1510 mm	1953 x 908 x 1510 mm
Capacity (gross/net)		491/386 lt	651/ 512 lt	983 / 773 lt
Net Weight		200 kg	240 kg	340 kg
Refrigeration		Ventilated		
Refrigerant		R290 / GWP3		
Climate Class		3M1		
Operating Conditions		25 °C / 60 %RH		
Temperature Range		0 / + 2 °C		
Compressor		1 Hermetic		2 Hermetic
Defrost		Off Cycle		
Power Supply		230 V / 1 ph		
Power Amp at Plug <i>20A Plug supplied - 56 Series</i>		10	10	20
Lighting - Canopy		LED 4000K		
Number of Shelves		3	3	3
Dimensions - Shelf Line 1		350 x 94 mm	350 x 125 mm	350 x 188 mm (2 Shelves)
Dimensions - Shelf Line 2 + 3		400 x 94 mm	400 x 125 mm	400 x 188 mm (2 Shelves)
Dimensions Base		503 x 94 mm	503 x 125 mm	503 x 188 mm (2 Shelves)
Shelf Bracket Adjustment		0°, 10°, 20°		
Shelf Lighting - Undershef		LED 4000K		
Shelf Merchandising		H30 Plexiglass Product Stop Price Holder with Ticket Strip		
Closing System		Open Front - Self Rolling Curtain		
Swivel Castors with Brakes Standard <i>Leveling Feet Optional</i>		STD	STD	STD
Exterior Colour <i>Ex Works RAL options available</i>		RAL 9005 JET BLACK - Standard		
Interior Colour <i>Ex Works RAL options available</i>		RAL 9005 JET BLACK - Standard		
End Panel		Panoramic (25mm)	Solid (34mm)	Solid with Mirror (34mm)
Standard Configuration		REFRIGERANT - R290 LIGHTING - Canopy & Under Shelf 4000K END PANELS - Panoramic CLOSING SYSTEM - Open Front BASE - Swivel Castors		

