

# Oblique H205 Smartflex TN



H 205

P 78

L 94 • 125 • 188

meat • sandwiches • drinks • dairy • fresh products

Automatic opening glass door semi-vertical chiller, with smartflex door system for contactless shopping. Fitted with an environmentally friendly plug-in R290 refrigeration system for the display of dairy products, meat, fresh and pre-packed products.

#### Installation

Plug-in

#### Cabinet front height

462

#### Configuration

Smartflex Automatic Door  
Multideck

#### Refrigerant

R290

#### Refrigeration System

Removeable Cassette -  
Ventilated (RV)

#### Compressor

Hermetic

#### Defrost

Off cycle

#### Temperature range

+2 / +4 °C

#### Climate class

3M1

#### Operating conditions

25°C Ambient / 60% RH

#### Power Supply

230V / 1 Ph / 50Hz

#### Electrical Amperage

Connection 94

10A

#### Electrical Amperage 125

10A

#### Electrical Amperage 188

20A

#### Closing System

SMARTFLEX AUTO-OPENING

#### Closing System

Smartflex Auto Glass Doors

#### Side panels

- Panoramic End Panel - safety glass (Std)
- Solid Mirror End Panel (Optional)

#### Shelves no.

5 with LED (Lighting Standard)

#### Shelves type

Solid

#### Shelves fence

Solid

#### Lighting

- 4000k LED lighting on canopy (Std)
- 4000k Undershelf LED Shelf Lighting (Std)
- 3000K LED Colour (Optional)

#### Inside Colour

- RAL 9005 - Jet Black (Std)
- RAL color choice - Factory Option
- Stainless Steel - Factory Option

#### Outside colour

- RAL 9005 - Jet Black (Std)
- RAL color choice - Factory Option
- Stainless Steel - Factory Option

#### Side panels' colour

- RAL 9005 - Jet Black (Std)
- RAL color choice - Factory Option
- Stainless Steel - Factory Option
- 4000K Standard

#### Base

- Castors with brake (Std)
- 4 adjustable feet (optional)



Multideck Display with Smartflex Automatic Opening Doors  
Removeable R290 Cassette

#### Inside colour



#### Outside colour



#### Side panels colour



RAL colour system or stainless steel options available ex. factory \*POA



## Oblique H205 Smartflex TN

		94	125	188
External dimensions PANORAMIC (LxDxH)	Swivel Castors	993 x 780 x 2123 mm	1300 x 780 x 2123 mm	1935 x 780 x 2123 mm
	Adjustable Feet	993 x 780 x 2050 mm	1300 x 780 x 2050 mm	1935 x 780 x 2050 mm
External dimensions SOLID (LxDxH)	Swivel Castors	1011 x 780 x 2123 mm	1318 x 780 x 2123 mm	1953 x 780 x 2123 mm
	Adjustable Feet	1011 x 780 x 2050 mm	1318 x 780 x 2050 mm	1953 x 780 x 2050 mm
Capacity (gross/net)		396 / 355 lt	754 / 453 lt	1129 / 665 lt
Net weight		285 kg	345 kg	485 kg
Refrigeration		Ventilated		
Refrigerant		R290 / GWP3		
Climatic class		3M1		
Operating conditions		25 °C / 60 %RH		
Temperature range		-1 / +5 °C		
Compressor (q.ty-type)		1 Hermetic		2 Hermetic
Defrost		Off Cycle		
Power supply		230 V / 1 ph		
Power Amp at Plug <i>20A Plug supplied - 56 Series</i>		10	10	20
Lighting - Canopy		LED 4000K		
Number of Shelves included per cabinet		5	5	5
Dimensions - Shelf Line 1		350 x 94 mm	350 x 125 mm	350 x 188 mm (2 Shelves)
Dimensions - Shelf Line 2 + 3		350 x 94 mm	350 x 125 mm	350 x 188 mm (2 Shelves)
Dimensions Base		382 x 94 mm	382 x 125 mm	382 x 188 mm (2 Shelves)
Shelf Bracket Adjustment		0°, 10°, 20°		
Shelf Lighting - Undershef		LED 4000K		
Shelf Merchandising		H30 Plexiglass Product Stop   Price Holder with Ticket Strip		
Closing System		Smartflex Auto-Opening - Single Glass Wings		
Swivel Castors with Brakes Standard <i>Leveling Feet Optional</i>		STD	STD	STD
Exterior Colour <i>Ex Works RAL options available</i>		RAL 9005 JET BLACK - Standard		
Interior Colour <i>Ex Works RAL options available</i>		RAL 9005 JET BLACK - Standard		
End Panel		Panoramic (25mm)	Solid (34mm)	Solid with Mirror (34mm)
Configuration		Refrigerant - Refrigerant - R290   LIGHTING - Canopy & Under Shelf 4000K   END PANELS - Panoramic   CLOSING SYSTEM - Smartflex Auto   BASE - Swivel Castors		

