

Panda TB Freezer



H 205 • 225

P 85

L 125 2p • 188 3p

frozen food & ice cream

Glass door freezer in matching profile to our Panda multideck chillers, fitted with an environmentally friendly plug-in R290 refrigeration system for the display of frozen foods and ice cream.

Installation

- Plug-in Air Cooled Standard
- Water Cooled POA Option

Configuration

Glass Door Multideck Freezer

Refrigerant
R290

Refrigeration System
Ventilated (RV)

Compressor
Hermetic

Defrost
Hot Gas

Temperature Range
- 23 / - 25 °C

Climate Class
3L1

Operating Conditions
25°C Ambient / 60% RH

Power Supply
230V / 1 Ph / 50Hz

Electrical Amperage 2P
20A

Electrical Amperage 3P
20A

Closing System
Hinged Glass Doors - Triple Glass

Side Panels

- Solid End (Std)
- Panoramic (Heated) (P.O.A)

Shelves no.

- H205 - 4 Shelves
- H225 - 5 Shelves

Shelves Type
Solid

Shelf Fence
Perspex H30

Lighting
Side & Mullion LED 5700k

Inside Colour

- RAL 9005 - Jet Black (Std)
- RAL Colour Choice - Factory Option

Outside Colour

- RAL 9005 - Jet Black (Std)
- RAL Colour Choice - Factory Option

Side Panels Colour

- RAL 9005 - Jet Black (Std)
- RAL Colour Choice - Factory Option

Base/ Equipment Handling
4 adjustable feet

Inside Colour
 RAL optional

Outside Colour
 RAL optional

Plinth Colour
 RAL optional

RAL colour system options available ex. factory *POA



Glass Door Freezer



Panda TB Freezer		125 2p	188 3p
External Dimensions PANORAMIC (LxDxH)	P85 / 205	1350 x 850 x 2100 mm	1980 x 850 x 2100 mm
	P85 HT / 225	1350 x 850 x 2300 mm	1980 x 850 x 2300 mm
Capacity (gross/net)	P85 / 205	1308 / 955 lt	1962 / 1432 lt
	P85 HT / 225	1490 / 1088 lt	2236 / 1632 lt
Net Weight	P85 / 205	471 kg	707 kg
	P85 HT / 225	508 kg	762 kg
Refrigeration	Ventilated		
Refrigerant	R290 / GWP3		
Climate Class	3L1		
Operating Conditions	25 °C / 60 % RH		
Temperature Range	- 18 / - 16 °C		
Compressor	1 Hermetic	2 Hermetic	
Defrost	Hot Gas- Manual Condensate		
Power Supply	230 V / 1 ph / 50 Hz		
Power Amp - Appliance to be Hard Wired on site	20	20	
Lighting - Canopy	LED 5700K		
Number of Shelves	P85 / 205	4	4
	P85 HT / 225	5	5
Shelf - Grid Type - Dimension Depth	450mm	450mm	
Dimensions Base	536mm	536mm	
Shelf Bracket Adjustment	0°, 10°, 20°		
Vertical LED Lighting	LED 5700K		
Shelf Merchandising	Price Holder with Ticket Strip		
Closing System	Triple Glazed Hinged Glass Doors		
Leveling Feet - Mandatory	Mandatory		
Exterior Colour <i>Ex Works RAL options available</i>	RAL 9005 JET BLACK - Standard		
Interior Colour <i>Ex Works RAL options available</i>	RAL 9005 JET BLACK - Standard		
End Panel	Panoramic Glass (50 mm)	Solid (50mm) STD	
Configuration	REFRIGERANT - R290 LIGHTING - Canopy & Vertical LED 5700K END PANELS - SOLID CLOSING SYSTEM - Glass Door BASE - Leveling Feet		

